



NOTES:

1. TO BE USED WITH DOT 3, 4 OR 5 BRAKE FLUID ONLY.
2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE TO BE USED FOR REFERENCE PURPOSES ONLY. MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
3. THE PRESSURE SWITCH IS SURROUNDED BY A SILICONE SEALANT IN THIS APPROXIMATE LOCATION.
4. LOW PRESSURE WARNING SWITCH, UNION AND TEE MAY BE SHIPPED UNASSEMBLED. TORQUE COMPONENTS TO 9-15 LBFT.

PERFORMANCE CHARACTERISTICS:

1. MAXIMUM WORKING PRESSURE: 2000 PSI
2. FOR USE IN 12 VOLT APPLICATION.
3. LOW PRESSURE WARNING SWITCH SPECIFICATIONS:
 - CONTACT ARRANGEMENT: NORMALLY CLOSED
 - RATING: 30 AMP, 6VDC
 - 20 AMP, 12 VDC
 - PRESSURE SETTING: CONTACTS OPEN BY 700 PSI INCREASING
 - RELEASE: -10% OF SETTING
 - OPERATING TEMPERATURE: -20 °F TO 250 °F
4. ARMING SWITCH/COIL SPECIFICATIONS:
 - SWITCH CONTACTS: N.O., CLOSE BETWEEN 50 TO 100 PSI.
 - COIL RESISTANCE: 3 OHMS

SERVICE PARTS:

1. LOW PRESSURE WARNING SWITCH P/N 20-580-051.
2. BRAKE LOCK P/N 01-620-001.

**INCH
[MILLIMETER]**

MICO North Mankato, Minnesota USA				
SCALE 1.000	TITLE BRAKE LOCK			
DWN MAP 2008-06-18	APVD PROD ENGRG DPD 2008-06-23	SIZE B	DRAWING NUMBER 02-620-009	REV H
X NO .	APVD ENGRG BSW 2008-06-18		CUSTOMER COPY	0 3

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.