

- NOTES:
 1. INTENSIFIER TO BE USED WITH MINERAL BASE HYDRAULIC OIL ONLY.
 2. ACTUATOR TO BE USED WITH DOT 3, 4 OR 5 BRAKE FLUID ONLY.
 3. DIMENSIONS WITHOUT TOLERANCES MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY. MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
 4. REPAIR KIT P/N 02-400-045.
 5. SURFACE FINISH: PRIMER PAINT.

PERFORMANCE CHARACTERISTICS: 1. INTENSIFIER RATIO: 2:1 APPROXIMATE LARGE BORE - Ø1.625 INCHES. SMALL BORE: Ø1.125 INCHES. 2. EFFECTIVE STROKE - 1.44 INCHES. 3. 15 PSI AT INLET WILL CLOSE RESERVOIR PORT.

INCH [MILLIMETER]

	COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO,	MICO, INC. CLAIMS PROPRIE
	INC. ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL	THE MATERIAL DISCLOSED IN
	USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR	THIS DOCUMENT IS PROVIDED
	DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF	AND MAY NOT BE REPRODUCE
	COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON	WITHOUT WRITTEN PERMISSION
	AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.	COPYRIGHT MICO, INC. ALL F
-		

