



OPTIONAL MOUNTING
SCALE 0.375

- NOTES:

 1) TO BE USED WITH MINERAL BASE HYDRAULIC OIL ONLY.

 2) DIMENSIONS MAY VARY BETWEEN UNITS AND ARE TO BE USED FOR REFERENCE PURPOSES ONLY. MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.

 3) SLOWLY APPLY GREASE THRU ZERK FITTING AFTER ASSEMBLY UNTIL GREASE IS OBSERVED EXITING SEALS. OVER PRESSURIZING MAY FORCE SEALS OUT OF HOUSING.

 4) BRAKE SHOWN IN APPLIED POSITION.

 5) SET SCREW AND NUT TO BE SHIPPED UNASSEMBLED TO BRAKE.

 6) BRAKE SURFACE FINISH: ZINC CHROMATE YELLOW PER ASTM B633. TYPE II. SC2

 7) LINING MATERIAL: NON-ASBESTOS, LEAD FREE.

 8) SEAL KIT P/N 02-500-058.

 9) REPAIR KIT P/N 12-501-407.

 10) LINING KIT P/N 20-060-116.

- PERFORMANCE CHARACTERISTICS:

 1) BRAKE TORQUE: Bf (LBS-IN) = 1920 X (DISC RADIUS 1.18)

 2) MAXIMUM TORQUE AHCIEVED ONLY AFTER BRAKE HAS BEEN PROPERLY ADJUSTED AND BURNISHED.

 3) COMPLETE RETRACTION PRESSURE: 1,000 PSI.

 4) MAXIMUM CONTINUOUS DUTY PRESSURE IS 2,000 PSI.

 5) MAXIMUM INTERMITTENT PRESSURE IS 2,500 PSI.

 6) VOLUME REQUIRED FOR COMPLETE RETRACTION: .50 CU IN. MAXIMUM.

 7) CAUTION: DISC RUBBING SPEED SHOULD NOT EXCEED 5,000 FT./MIN.

 8) "A" DIMENSION = DISC RADIUS + 1.62 (DISC DIA. FROM 9 TO 15 INCHES.)

 "A" DIMENSION = DISC RADIUS + 1.75 (DISC DIA. GREATER THAN 15 INCHES.)





COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL THE MATERIAL DISCLOSED IN THIS DOCUMENT. USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC.

THIS DOCUMENT IS PROVIDED IN CONFIDENCE AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

	· ·					
0	SCALE 0.500	TITLE SPRING BRAKE				
E D	DWN JJH 2015-11-24	APVD PROD ENGRG PJS 2015-11-30	SIZE	DRAWING		REV
:.).	X NO x6698	APVD ENGRG BSW 2015-11-24	В	02-530-314 CUSTOMER COPY		K