



NOTES:

1. USE MINERAL BASE HYDRAULIC OIL ONLY FOR BRAKE RELEASE
2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY
MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES
3. LINING REPAIR KIT P/N 20-060-083
4. O-RING REPAIR KIT P/N 02-500-153
5. SPRING REPAIR KIT P/N 02-500-154

SPECIFICATIONS:

| | |
|-----------------------------|--|
| TYPE: | DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE |
| TORQUE RATING: | 1,500 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE ACTUAL TORQUE MAY VARY BY UP TO 10% DUE TO MANUFACTURING TOLERANCES. |
| RELEASE PRESSURE: | 70 PSI INITIAL, 95 PSI FULL |
| MAXIMUM OPERATING PRESSURE: | 3,000 PSI |
| MAXIMUM SPEED: | 1,000 RPM |
| LINING MATERIAL: | SINTERED BRONZE |
| APPROXIMATE WEIGHT: | 18 LB |

INCH
[MILLIMETER]

| | | | | |
|---|--------------------------------------|------|----------------|-----|
| MICO North Mankato, Minnesota USA | | | | |
| SCALE | TITLE | SIZE | DRAWING NUMBER | REV |
| 0.500 | MN-1315 CLOSED OUTPUT MOTOR BRAKE | B | 02-550-214 | A |
| DWN RGS1 2011-12-19 | APVD PROD ENGRG PJS 2011-12-28 | | | |
| X NO X11-5163 | APVD ENGRG RV 12/20/2011 | | CUSTOMER COPY | |

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.