

7. STALK ARKANGEMEN: RUTURZIATURZETIATURZETATURZETATURZETA B. BRAKE SURFACE COATING: GREY GLOSSY POLYURETHANE PAINT.
9. SPRING COMBINATION: 8 RED SPRINGS
10. RECOMMENDED CASE OIL: CHEVRON DELO GEAR LUBRICANT ESI SAE 80W-90. GEAR LUBRICANTS CONTAINING SULFUR-PHOSPHORUS BASED EP ADDITIVES SHOULD BE AVOIDED DUE TO LONG TERM EFFECTS ON FRICTION MATERIAL.

SPECIFICATIONS:

WET MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE.

4.000 RPM SHAFT SPEED CAPABILITY SPECIFIED IS FOR BRAKE IN RELEASED CONDITION. ENERGY ABSORPTION DURING APPLY CYCLE MUST BE CAREFULLY EXAMINED FOR EACH APPLICATION. MAXIMUM SPEED:

RELEASE PRESSURE: 200 PSI INITIAL, 240 PSI FULL, 3,000 PSI MAX.

LINING MATERIAL:

TORQUE RATING:

1.600 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE ACTUAL TORQUE MAY VARY BY UP TO 10% DUE TO MANUFACTURING TOLERANCES.

VOLUME OF OIL REQUIRED: TO RELEASE BRAKE

0.5 IN.³ MIN., 0.9 IN.³ MAX.

APPROXIMATE WEIGHT: 25 LB

INCH [MILLIMETER]



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS T THE MATERIAL DISCLOSED IN THIS DOCUMENT THIS DOCUMENT IS PROVIDED IN CONFIDENC COPYRIGHT MICO, INC. ALL RIGHTS RESERVED

	SCALE	TITIF	SLME	3-131324-BZ	
TO T.	0.500 MULTIPLE DISC BRAKE				
CE	DWN SHYPO		SIZE	DRAWING NUMBER	REV
E D	2014-10-08	PJS 2015-01-28	_	00 557 750	
С.	X NO	APVD ENGRG	В	02-556-450	-
D.		RV 10-09-2014		CUSTOMER COPY	1