

## **SPECIFICATIONS:**

TYPE: WET MULTIPLE DISC BRAKE. SPRING APPLY HYDRAULIC RELEASE.

RELEASE PRESSURE:

270 PSI INITIAL. 325 PSI FULL 2000 PSI MAX. CONTINUOUS

18.000 LBIN STATIC (BREAKAWAY) AT O PSI BACK PRESSURE TORQUE RATING:

2.0 IN<sup>3</sup> MAX. RELEASE VOLUME: LINING MATERIAL: SINTERED BRONZE MAXIMUM SPEED: 3.200 RPM APPROXIMATE WEIGHT: 92 LB

## COOLING OIL RECOMMENDATIONS

MINERAL BASE HYDRAULIC OIL TYPE:

OIL SUCH AS MOBIL DTE 24.

CITGO A/W 32 OR EQUIVALENT FLOW THRU CAPACITY: 3.8 TO 26.5 L/min (1.0 TO 7.0 GPM)

MAXIMUM CASE PRESSURE: 1.03 BAR (15 PSI)

SUMP OIL VOLUME:

HORIZONTAL SHAFT: 236.6 mL (8 FL. 0Z.) VERTICAL SHAFT: CONTACT FACTORY

NOTES:

BRAKES ARE SHIPPED DRY AND CUSTOMER IS RESPONSIBLE FOR ADDING PROPER TYPE AND VOLUME OF COOLING OIL

## **INCH** [MILLIMETER]



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC.

THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. | COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

	SCALE	TITLE	DΕ	3-505018	
•	0.500	DRIVELINE BRAKE			
	DWN RGBS1	APVD PROD ENGRG	SIZE	DRAWING NUMBER	REV
,	2010-03-26	PJS 2010-05-06	R	02-560-108	l <sub>D</sub>
	X NO x06-1082	APVD ENGRG RV 2010-04-27	D	CUSTOMER COPY	D 2
				COSTOMER COLL	l