

SPECIFICATIONS:

TYPE: WET MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE.

RELEASE PRESSURE: 2000 PSI MAX. CONTINUOUS

25.000 LBIN STATIC (BREAKAWAY) AT O PSI BACK PRESSURE TORQUE RATING:

2.0 IN³ MAX RELEASE VOLUME: LINING MATERIAL: SINTERED BRONZE MAXIMUM SPEED: 3.200 RPM APPROXIMATE WEIGHT: 90 LB

COOLING OIL RECOMMENDATIONS

OIL TYPE: MINERAL BASE HYDRAULIC

OIL SUCH AS MOBIL DTE 24.

CITGO A/W 32 OR EQUIVALENT FLOW THRU CAPACITY: 3.8 TO 26.5 L/min (1.0 TO 7.0 GPM)

MAXIMUM CASE PRESSURE: 1.03 BAR (15 PSI)

SUMP OIL VOLUME:

HORIZONTAL SHAFT: 236.6 mL (8 FL. 0Z.) VERTICAL SHAFT: CONTACT FACTORY

NOTES:

BRAKES ARE SHIPPED DRY AND CUSTOMER IS RESPONSIBLE FOR ADDING PROPER TYPE AND VOLUME OF COOLING OIL

INCH IMILLIMETER



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

DB-505025 TITLE SCALE DRIVELINE BRAKE 0.500 APVD PROD ENGRG DWN RGBS1 SIZE DRAWING NUMBER REV 2010-04-27 PJS 2010-05-06 02-560-110 X NO APVD ENGRG X06-1082 RV 2010-04-29 CUSTOMER COPY