

NOTES:

1. TO BE USED WITH DOT 3, 4 OR 5 BRAKE FLUID ONLY.

- 2. DIMENSIONS WITHOUT TOLERANCE MAY VARY BETWEEN UNITS AND ARE TO BE USED FOR REFERENCE PURPOSES ONLY. MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
- 3. FOR USE IN 24 VOLT APPLICATION.
- THE PRESSURE SWITCH IS SURROUNDED BY A SILICONE
 - SEALANT IN THE APPROXIMATE AREA.
- 5. PRESSURE P/N 20-580-051.
- 6. PRESSURE SWITCH MAY BE SHIPPED UNASSEMBLED TO BRAKE LOCK.

PERFORMANCE CHARACTERISTICS:

- 1. PRESSURE SWITCH SPECIFICATIONS: -CONTACT ARRANGMENT: NORMALLY CLOSED.
 - -RATING: 30 AMP, 6 VDC
 - 20 AMP, 12 VDC -PRESSURE SETTING: CONTACTS OPEN BE 700 PSI INCREASING.
 - -RELEASE: -10% OF SETTING.

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC. ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC. CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.



SCALE 1.000	TITLE BRAKE LOCK			
	APVD PROD ENGRG DPD 2016-07-19 APVD ENGRG		DRAWING NUMBER 02-620-173	RE\ H
× NO	BSW 2016-05-26	\wedge	CUSTOMER COPY	2 2