

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRI INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. COPYRIGHT MICO, INC. ALL

NOTES:

1. FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.

- 2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
- 3. REPAIR KIT P/N 12-400-002.
- 4. ACTUATOR ASSEMBLY P/N 12-460-188.
- 5. SURFACE FINISH: STEEL COMPONENTS ZINC PLATED PER ASTM B633 ALUMINUM COMPONENTS ARE UNPLATED.

PERFORMANCE CHARACTERISTICS: 1. MAXIMUM DISPLACEMENT: .727 CUIN

2. BORE SIZE: Ø1.25 IN

- 3. MAXIMUM OPERATING PRESSURE 425 PSI AT 85 LB PEDAL EFFORT.
- 4. PEDAL EFFORT NOT TO EXCEED 85 LB AT TOP OF PEDAL.

drawing number 12-460-186
NPI OR ECN NO
ECN H000184

INCH [MILLIMETER]

	North Mankato, Minnesota USA					
RIETARY RIGHTS TO	SCALE TITLE 0.500 PEDAL ACTUATOR					
IN THIS DOCUMENT. DED IN CONFIDENCE UCED OR DISCLOSED	DWN ETM 2016-01-21	APVD PROD ENGRG PJS 2016-03-14	SIZE	DRAWING NUMBER	REV	
ION FROM MICO, INC. LL RIGHTS RESERVED.	X NO	APVD ENGRG BSW 2016-02-19	В	12-460-186 customer copy	2 2	