


**NOTES:**

1. TO BE USED WITH MINERAL BASE HYDRAULIC OIL ONLY.
2. DIMENSIONS WITHOUT TOLERANCE MAY VARY BETWEEN UNITS AND ARE TO BE USED FOR REFERENCE PURPOSES ONLY. MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
3. PEDAL ACTUATOR P/N 12-460-186.  
ACTUATOR ONLY P/N 12-460-188  
BORE:  $\varnothing 1.250$  IN  
DISPLACEMENT: .73 CUIN  
REPAIR KIT P/N 12-400-002  
MAXIMUM OPERATING PRESSURE 425 PSI AT 85 LB PEDAL EFFORT.  
PEDAL EFFORT NOT TO EXCEED 85 LB AT TOP OF PEDAL.
4. SLAVE CYLINDER P/N 12-120-010  
BORE:  $\varnothing 0.625$  IN  
STROKE: 2.44 IN  
DISPLACEMENT: .73 CUIN  
REPAIR KIT P/N 12-100-010
5. RESERVOIR P/N 20-920-006  
CAPACITY: 3.30 CUIN
6. SYSTEM REPAIR KIT P/N 12-400-012

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

INCH  
(MILLIMETER)

 North Mankato, Minnesota USA		SCALE	TITLE		
		0.500	THROTTLE CONTROL		
DWN ETM	APVD PROD ENGRG	SIZE	DRAWING NUMBER	REV	
2016-01-21	PJS 2016-03-14	B	12-460-192	J	
X NO	APVD ENGRG		CUSTOMER COPY	2 2	
	BSW 2016-02-19				