





NOTES:

1. USE MINERAL BASE HYDRAULIC OIL ONLY FOR BRAKE RELEASE
2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY.
MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.

3. REPAIR KIT P./N 12-501-405 4. BRAKE SURFACE COATING: BLACK SEMI GLOSS ACRYLIC PRIMER

SPECIFICATIONS:

DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE

MAXIMUM SPEED:

4.000 RPM SHAFT SPEED CAPABILITY SPECIFIED IS FOR BRAKE IN RELEASED CONDITION. ENERGY ABSORPTION DURING APPLY CYCLE MUST BE CAREFULLY EXAMINED FOR EACH APPLICATION.

RELEASE PRESSURE: 380 PSI INITIAL, 440 PSI FULL, 3,000 PSI CONTINUOUS MAX.

4.000 PSI INTERMITTENT.

LINING MATERIAL: HIGH PERFORMANCE COMPOSITE, NON-METALLIC BASED

TORQUE RATING: 6.000 LBIN STATIC (BREAKAWAY)

STATIC TORQUE MAY VARY $\pm 10\%$ FROM SPECIFIED VALUE DUE TO MANUFACTURING TOLERANCES.

VOLUME OF OIL REQUIRED TO RELEASE BRAKE: 0.5 IN 3 MIN. & 0.9 IN 3 MAX.

APPROXIMATE WEIGHT: 19 LB INSTALLATION INFORMATION

1. THIS BRAKE IS DESIGNED FOR USE WITH
CHAR-LYNN MOTORS CONTAINING AN INTERNAL CASE DRAIN.
2. IF THE MOTOR CASE DRAIN IS USED. THE DRAIN LINE MUST
BE ROUTED SUCH THAT THE SPLINE AREA IS LUBRICATED
AT ALL TIMES.
3. REFER TO THE MOTOR INSTALLATION INSTRUCTIONS FOR

FURTHER INFORMATION.

CASE PRESSURE BETWEEN THE MOTOR AND BRAKE MUST NOT EXCEED 100 PSI.

INCH [MILLIMETER]

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.



TITLE COMPACT DESIGN GB-141260-L2 B-MOUNT MULTIPLE DISC BRAKE 0.500 DWN SHYP APVD PROD ENGRG DRAWING NUMBER PJS 2015-09-28 13-100-044 APVD ENGRO RV 2015-08-27 CUSTOMER COPY