

INCH

[MILLIMETER]

## NOTES:

1. USE MINERAL BASE HYDRAULIC OIL ONLY FOR BRAKE RELEASE.
2. DIMENSIONS WITHOUT TOLERACES MAY VARY SLIGHTLY AND ARE FOR REFERENCES PURPOSE ONLY.
MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
3. O-RING REPAIR KIT P/N 12-501-295

BEARING REPAIR KIT P/N 12-501-094

5. SPRING REPAIR KIT P/N 12-501-294 6. LINING REPAIR KIT P/N 12-501-371

**SPECIFICATIONS:** 

WET MULTIPLE DISC BRAKE, (WITH ONE WAY CLUTCH)

SPRING APPLY, HYDRAULIC RELEASE.

2.000 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE ACTUAL TORQUE MAY VARY BY UP TO 10% DUE TO MANUFACTURING TOLERANCES. TORQUE RATING:

RELEASE PRESSURE: 95 PSI INITIAL. 110 PSI FULL

MAXIMUM OPERATING PRESSURE: 3.000 PSI MAXIMUM SPEED: 1,400 RPM. LINING MATERIAL: NON METALLIC APPROXIMATE WEIGHT: 43 LB MAXIMUM OPERATING TEMPERATURE: 270° F

## COOLING OIL RECOMMENDATIONS

DEXRON 3 AUTOMATIC OIL TYPE: TRANSMISSION FLUID

FLOW THRU CAPACITY: 1.0 - 7.0 GPM MAXIMUM CASE PRESSURE: 30 PSI

SUMP OIL VOLUME: 6 FL, 0Z, BRAKE IS DESIGNED FOR HORIZONTAL USE ONLY

## CAUTION:

OTES CONTAINING SLIPPERY OR ANTI-WEAR ADDITIVES, SUCH AS GRAPHITE OR MOLYBDENUM DISULFIDE, OR EXTREME PRESS. (E.P.) TYPE LUBRICANTS SHOULD NOT BE USED AS COOLING OIL, THESE LUBRICANTS MAY ALLOW THE BRAKE TO SLIP AT TORQUE LEVELS BELOW THE RATED VALUES.

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

## NOTE:

BRAKE MOUNTS TO MOTOR USING M12 SOCKET HEAD CAP SCREWS



TITLE WINCH BRAKE 0.500 DRAWING NUMBER DWN SHYF APVD PROD ENGRG PJS 2016-02-26 13-602-026 APVD ENGR RV 2016-02-15 CUSTOMER COPY

01-JAN-2012