

PERFORMANCE CHARACTERISTICS:

- 1) NORMALLY CLOSED CONTACT TO OPEN AT 2000 PSI INCREASING (MAX.)
   NORMALLY CLOSED CONTACT TO RECLOSE AT 1600 PSI OR GREATER (DECREASING).
- SWITCH DIFFERENTIAL IS 400 PSI MAX.
- 2) WEATHER RESISTANT ADJUSTABLE PRESSURE SWITCH:
  - PROOF PRESSURE: 15,000 PSI.
  - LEAD WIRE LENGTH: 16" APPROXIMATE.
  - WIRE CODE: BLACK COMMON

RED - NORMALLY CLOSED

WHITE OR GREEN - NORMALLY OPEN

- 3) SWITCH SPECIFICATIONS:
  - MICRO SWITCH P/N 11SM3.
  - SINGLE POLE DOUBLE THROW.

RATED											
12	VDC		30	) VDC		12	25	VAC	25	50	VAC
3	AMPS	INDUCTIVE	3	AMPS	INDUCTIVE	5	A	MPS	5	A١	1PS
5	AMPS	RESISTIVE	5	AMPS	RESISTIVE						

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC. ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC. CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

		a <b>WABCO</b> company
ΛΙ	Г	TITIC

SCALE 1,000	TITLE	DDFCC	URF SWITCH	
DMN Hrr			DRAWING NUMBER	REV
2017-10-17 X NO	DPD 2018-05-14 APVD FNGRG	Α	20-580-084	G
	BSW 2017-10-23	, ,	CUSTOMER COPY	1 1