



PRODUCT BULLETIN

"C" Mount Hydraulic Apply, Spring Release Clutch (wet)

DESCRIPTION

The MICO® Multiple Disc Clutch is a split shaft design with a standard SAE C mounting pattern for ease of installation. Flow through oil cooling is required for increased energy capacity, lubrication of internal components, and dissipation of heat from the clutch pack during engagement. Metallic linings are used for increased life.

A secondary oil source modulates the operation of the clutch. When pressure is applied to the activation port, an engagement torque proportional to the applied pressure is generated. Springs are used to disengage the clutch when pressure is removed.

A typical application would be to install the clutch between a gearbox and a pump, providing engagement or disengagement of the pump, only when required for secondary operations. Another application might be to install the clutch between a hydraulic motor and wheel drive for auxiliary power control, when needed.

FEATURES

- Split shaft design standard SAE C mounting configuration for easy installation
- Flow-through oil cooling for high capacity
- Metallic linings for long life
- Spring release minimizes heat generation in disengaged mode
- Perfect for pump disconnect or PTO controls
- Oil or pneumatic actuation



SPECIFICATIONS

Torque rating.....	1130 N-m @ 22.8 bar (10,000 lbin @ 330 PSI) input pressure)
Maximum input pressure	24.1 bar (350 PSI)
Fluid displacement.....	16.4 cm ³ (1.0 in ³) minimum 29.5 cm ³ (1.8 in ³) maximum
Maximum speed (clutch engaged)	3000 RPM
(clutch disengaged).....	3000 RPM
Coolant flow.....	18.9 L/min (5 GPM) maximum
Case pressure	0.69 bar 10 PSI maximum
Approximate weight	236.6 N (53 lb)

For use with mineral base hydraulic oil only.

This document is intended to provide general information about MICO Products. MICO, Inc. has attempted to present accurate information about MICO Products in its catalogs, brochures, and other printed materials. MICO, Inc. is not responsible for errors, inaccuracies, or inconsistencies that may exist in any catalog brochure or other printed materials or any damages arising from or related to reliance on information in them. Materials and specifications for MICO Products set forth in catalogs, brochures, and other printed materials are subject to change without notice or obligation. Refer to www.mico.com for the most recent versions of our literature. If you have any questions concerning MICO Products, please contact MICO, Inc. All MICO Products and service are sold and provided subject to the MICO Warranty at www.mico.com in effect on the date of sale or supply.

MICO is a trademark and registered trademark of MICO, Inc. MICO is registered in the U.S. Patent and Trademark Office as well as in Australia, Canada, Indonesia, Japan, Peoples Republic of China, South Korea, and the European Community.



MICO, Inc.

1911 Lee Boulevard
North Mankato, MN U.S.A. 56003-2507
Tel: +1 507 625 6426 Fax: +1 507 625 3212

